

Fast, Low Cost and Ultrasonic Technology for Flexible Welding Processes

TOCHI



ERUJ-05

Digital Ultrasonic Generator


High frequency 20 kHz used in mask productionAvailable with 2000 W

Power Output and 2 years warranty.


- Ability to High Production
- Continuous Welding Process
- Non-Contact Welding and Weaving
- Automated Easy Integration
- Production Processes
- Soft and Elastic Surfaces Skin-Friendly Products

Ultrasonic Generator

Horn Mould



Utrasonic Welding Transducer



TECHNICIAL SPECIFICATIONS

: TOCHI - ERUJ-05 Digital Ultrasonic Generator Model

Frequency : 20 kHz Ultrasonic Power : 2600 W

Energy Input : AC 220V, 50 Hz

Converter : Korea Technology LBT Piezoelectric Welding Tip

: Continuous welding mode! Digital Generator

* Continuous welding mode used for manual or semi-automatic mask machine.

* Continuous welding mode used for automatic mask machine.

* Continuous welding mode for fully automatic.

* The generator is the third generation of intelligent automatic frequency trackin

and enhancement.

: - Intelligent circuit layout design and wiring for better control source and Advantages

professional IC programming.

- LBTTransducer with piezoelectric ceramics more stable ultrasonic energy.

- It is widely used in the market. stable quality.

: Generator: 385x220x115mm Sizes

Horn: 110x20mm or 200x20mm

Gross Weight : 14 kg.

Package Length : 470x400x360 mm

Package Included : Ultrasonic Generator, Transducer, Horn, AC Cable, Trigger Cable

Warranty : 2 years

erpateknoloji.com







